

石墨、纖維、食品、鎂合金、鋁合金、碳粉、藥品、鐵屑、廢氣或油霧等任何粉塵皆適用。  
24小時免停機。品質不輸進口。88年設立至今，始終堅持品質穩定，服務客戶為最重要指標。  
郁錫為最專業集塵機製造商 食品、藥廠、半導體、機械廠最愛



● **CS-102** 移動式集塵機  
(自動逆衝濾心配備)



防爆集塵機  
● **CS-103** 移動式集塵機  
(針對低燃點、溫度高)




防爆集塵機  
● **NS-750** 透浦式集塵機  
(自動吹撥濾心、大風量)



● **CS-350** 自動吸粉、料機  
(粉末、顆粒皆可輸送)



● **NS-502** 高壓或透浦式集塵機  
(可移動、抽屜式設計)



● **NS-501** 袋式集塵機  
(如PCB板屑等大量粉塵適用)



● **NS-503** 高壓或透浦式集塵機  
(可移動、垃圾袋設計)



● **CS-106** 廢氣處理機  
(針對各種味道消除)



● **CS-105** 油霧處理機  
(油氣回收)



● **CS-104** 脈衝式篩粉機  
(針對大小顆粒分離)

# CS-102系列 專利287708號

## 高壓脈衝式集塵機

PULSED DUST COLLECTOR

全台首創自動逆洗之集塵機

超靜音 / 無須換濾袋

可24小時使用

石墨、纖維等皆可使用



### ■ CS-1021 透浦式脈衝集塵機 TURBO TYPE PULSED DUST COLLECTOR

型號(MODEL)	CS-1021	CS-1021	CS-1021	CS-1021	CS-1021	CS-1021	CS-1021	CS-1021
馬力(HP)	1	2	3	5	7.5	10	15	20
輸出功率(KW)	0.75	1.5	2.2	3.7	5.5	7.5	11	15
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	6	6	6	6	8	10	12	12
靜壓(mmAq)	270	320	380	400	450	500	550	550
材積(長x寬x高)cm	116x77x165	116x77x165	116x77x165	116x77x165	100x100x240	100x100x240	200x150x280	200x150x280
風量M3/mim(可選配)	18	22	40	45	65	75	120	150
音量db	65	70	75	75	85	85	85	85
容量L(可選配)	40	40	40	40	95	95	95	95
主機重量kg	74	81	90	109	298	310	850	853

### ■ CS-1022 多段式脈衝集塵機 MULTI-STAGE PULSED DUST COLLECTOR

型號(MODEL)	CS-1022	CS-1022	CS-1022	CS-1022	CS-1022	CS-1022	CS-1022	CS-1022	CS-1022
馬力(HP)	1	2	3	5	5	7	10	15	20
輸出功率(KW)	0.75	1.5	2.2	3.7	3.7	5.5	7.5	11	15
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	4	4	4	6	6	6	6	6	6
靜壓(mmAq)	450	700	900	790	1100	1050	1300	900	1000
材積(長x寬x高)cm	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160
風量M3/mim(可選配)	13	14	16	23	16.5	24	24	65	70
音量db	60	61	63	70	70	70	75	90	90
容量L(可選配)	40	40	40	40	40	40	40	40	40
主機重量kg	80	88	97	114	107	139	159	245	260

### ■ CS-1023 高壓式脈衝集塵機 HIGH-PRESSURE PULSED DUST COLLECTOR

型號(MODEL)	CS-1023	CS-1023	CS-1023	CS-1023	CS-1023	CS-1023	CS-1023	CS-1023	CS-1023
馬力(HP)	1	2	3	5	7	10	15	20	25
輸出功率(KW)	0.75	1.5	2.2	3.7	5.5	7.5	11	15	19
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	4	4	4	4	4	4	4	4	4
靜壓(mmAq)	1800	2500	2800	2800	3000	3000	3200	3200	3500
材積(長x寬x高)cm	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160
風量M3/mim(可選配)	2.2	4.5	6.2	8.3	9.5	11	22	24	24
音量db	60	65	65	67	74	74	76	76	76
容量L(可選配)	40	40	40	40	40	40	40	40	40
主機重量kg	72	82	87	107	250	260	350	357	365



## ■ 特點 Features

- 此機可作為中央集塵設備用，依現場口徑數量、粉塵多寡、搭配馬力大小、桶身大小。主機桶採用不鏽鋼304材質，耐用好清理。
- 採用旋風式離心力原理，將粉塵或顆粒吸入下桶。
- 鼓風機純屬抽風效用，吸入物質沒有直接接觸馬達，馬達耐用持久。
- 乾溼兩用，CS-1022、1023 可當一般吸塵器使用。
- 可24小時使用。
- 石墨、纖維、食品、碳粉、鋁粉、農藥、藥品等任何粉末，有無毒性皆可使用。
- 鐵屑或銅屑等金屬也可當回收桶，耐用好清理。
- 高壓脈衝噴射自動清理濾心中間粉塵，粉塵自動振落，可全天候使用。
- 全台首創自動逆衝濾心之集塵機，靜音、無須換濾袋。
- 濾心採用PET折疊式濾心材質，過濾面積大，任何細小粉末皆可使用。
- 只需將拉桿拉起，下桶抽出，即可清理粉塵。
- 各種馬力及大小規格皆有，可視情況需求來搭配。
- 濾心可過濾至0.1 $\mu$ m(micron)粉末。
- 附消音裝置，減少噪音汙染。
- 附壓力表，有無阻塞一目了然。
- This machine can be used as a central dust collection equipment, in accordance with the quantity of scene caliber, dust amount, with horsepower, barrel body size  
The main body is made from stainless steel 304, featuring long durability and easy to clean.
- Employ cyclonic centrifugal principle to suck powder or granule into bottom drum.
- The blower is applied for sucking air only. The sucked dusts do not directly contact with motor for increased service life of motor.
- For dry and wet applications, CS-1022, 1023 can be used as normal household vacuum cleaner.
- Allows for 24 hours operation.
- Suitable for poisonous or non-poisonous dusts such as graphite, fiber, food, carbon powder, aluminum powder, pesticide and medicine.
- Iron chips or copper chips can also be collected with maximum durability and easy cleaning.
- High pressure pulsated jet for automatically cleaning dusts existed in the center of filter core. Dusts are knocked off automatically, making it suitable for 24 hours operations.
- The innovative dust collector in Taiwan with automatically pulsated filter-core features silent operation without need to change filtering bag.
- The filter-core is manufactured from PET bellow type filtering element, providing greater filtering area.
- Applicable for any fine powder.
- Easy to clean by simply pulling out the pulling rod and remove the lower tank.
- Various motor horsepower and specification to meet specific requirement.
- The filter-core allows for filtering powder of up to 0.1 $\mu$ m(micron) .
- Equipped with sound buffering device for reducing noise.
- Equipped with pressure gauge for clearly checking if any jamming occurs or not.

貴公司若有相關問題(如另設計15HP以上 集塵機、集料方式、集塵罩、風量、入口口徑、材質、儲塵容量等)，歡迎來電洽詢，本公司可配合變更或提出更好解決方式。

If you have any specific requirements (such as dust collector with over 15 HP motor, collection method, dust hood, air flow, inlet port diameter material and storing capacity etc), contact us for further service. We will make design change or provide solutions for your requirements.



現場實績

# NS-750 二段式自動吹撥集塵機

AUTOMATIC SHIFTING AND BLOWING DUST COLLECTOR

全台首創一機兩段式除塵

(自動撥塵、吹塵))

防爆集塵機

石墨、纖維等皆可使用

超靜音/無須換濾袋

可24小時使用



## ■ NS-750 二段式自動吹撥集塵機

型號(MODEL)	NS-750	NS-750	NS-750	NS-750	NS-750	NS-750	NS-750	NS-750	NS-750
馬力(HP)	3	5	7.5	10	15	20	25	30	40
輸出功率(KW)	2.2	3.7	5.5	7.5	11	15	18.5	22	30
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	6	6	8	8	12	12	14	16	18
靜壓(mmAq)	380	400	500	500	550	550	550	550	550
材積(長x寬x高)cm	90x100x243	90x100x243	90x100x243	90x100x243	200x150x280	200x150x280	200x150x280	200x150x280	200x150x280
風量M3/mim	40	45	70	75	120	150	180	200	250
音量db	65	70	78	80	83	85	85	85	85
容量L(可選配)	95	95	95	95	95	95	95	95	95
主機重量kg	239	254	298	320	850	853	858	863	868

貴公司若有相關問題(如另設計15HP以上 集塵機、集料方式、集塵罩、風量、入口口徑、材質、儲塵容量等)，歡迎來電洽詢，本公司可配合變更或提出更好解決方式。

If you have any specific requirements (such as dust collector with over 15 HP motor, collection method, dust hood, air flow, inlet port diameter material and storing capacity etc), contact us for further service. We will make design change or provide solutions for your requirements.



## ■ 特點 Features

- 防爆集塵機，針對鎂粉、鋁合金等容易粉塵爆炸物質可另設計。
- 免人工清理濾心。
- 風量大，靜壓高。
- 渦輪式風機可24小時使用，不會產生高熱。
- 全台首創自動撥、吹沖濾心之集塵機，靜音、無須換濾袋。
- 石墨、纖維、食品、碳粉、鋁粉、農藥、藥品等任何粉末，有無毒性皆可使用。
- 濾心採用PET材質，可過濾至 $0.1\mu\text{m}(\text{micron})$ 粉末，過濾面積大，確保工作環境不受汙染，可乾濕兩用，安裝替換容易。
- 全自動清除濾心粉塵。集塵機濾心中間自動刮塵系統，可將濾心粉塵輕易刮落，同時瞬間會自動啟動風壓吹氣裝置系統，將濾心表面細小粉塵吹落，讓濾心不容易阻塞，提高濾心耐用度。
- 附消音箱裝置，減少噪音污染。
- 附壓力表，有無阻塞一目了然。
- 集塵機內部自動產生篩選氣流效應，石墨粉或纖維等物質會依照離心力原理直接掉入集塵桶，避免濾心受到異物碰撞，延長濾心之使用壽命。
- 大濾心採用PET折景式材質，更提高過濾面積，任何細小粉末皆可使用。
- 只需將扣環拉起，下桶移出，即可清理粉塵。(下桶附移動輪，移動使用方便)。
- 馬力7.5HP以上大小規格皆有，可視情況需求來搭配。
- 佔地空間小。
- 可另附手動吸塵裝置。
- Explosion-proof dust collector. For magnesium powder、aluminum alloy etc. The easy dust explosion substance another design.
- No manual cleaning of filter element is required.
- Great air flow. High static pressure.
- Turbo type air blower is excellent for 24 hours running without generation of high temperature.
- A dust collector designed with innovative automatic shifting and blowing the filter element in Taiwan. It also features noiseless running without need of changing filtrating bag.
- Applicable for various poisonous and non-poisonous powder dusts, such as graphite, fiber, food, carbon powder, aluminum powder, pesticide and medicine, etc.
- The filter element is manufactured of PET material with filtrating capacity up to  $0.1\mu\text{m}(\text{micron})$  of powder. Great filtrating area to prevent working environment from pollution. Suitable for dry and wet filtration and easy replacement.
- Automatic clear the Filter dust. Middle of dust collector the Filter with automatic scraper system, which can be easily scrape the Filter dust off, while instant air pressure blowing device will automatically start the system, the filter surface of small dust overblow, make the filter is not easily clog, improve durability of the Filter.
- Equipped with noise eliminating box to reduce noise.
- Equipped with pressure gauge for checking jamming condition with ease.
- The dust collector automatically creates an internal sieving air flow, that permits graphite powder or fiber directly drop into the dust collection tank according to centrifugal force principle. This prevents foreign objects from bumping against the filter element while extending its service life.
- The oversized filter element is manufactured from corrugated PET material to increase filtration area, which is suitable for tiny powder.
- The dust collect tank can be easily removed for cleaning by unbuckling the pull tab. (the tank is fitted with roller, easy to move).
- Motor horsepower over 7.5HP is available.
- Small space occupation.
- A variable to equip with manual dust collector.



現場實績



# CS-103系列 專利287708號

## 旋風式水過濾集塵機

WATER-LEACHABLE DUST COLLECTOR

防爆集塵機、鎂、鋁合金或燃點低、  
溫度高、拋光產品或粉塵量多、  
有黏性產品 可24小時使用

超靜音 / 無燃點問題 / 無須換濾袋



### ■ CS-1031 透浦式水過濾集塵機 TURBO TYPE WATER FILTERING DUST COLLECTOR

型號(MODEL)	CS-1031	CS-1031	CS-1031	CS-1031	CS-1031	CS-1031	CS-1031	CS-1031
馬力(HP)	1	2	3	5	7.5	10	15	20
輸出功率(KW)	0.75	1.5	2.2	3.7	5.5	7.5	11	15
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	6	6	6	6	8	10	12	12
靜壓(mmAq)	270	320	380	400	450	500	550	550
材積(長x寬x高)cm	116x77x160	116x77x160	116x77x160	116x77x160	100x100x240	100x100x240	200x150x280	200x150x280
風量M3/mim(可選配)	18	22	40	45	65	75	120	150
音量db	65	70	75	80	85	85	85	85
容量L(可選配)	40	40	40	40	95	95	95	95
主機重量kg	72	79	86	107	298	310	850	853

### ■ CS-1032 多段式水過濾集塵機 MULTI-STAGE WATER FILTERING DUST COLLECTOR

型號(MODEL)	CS-1032	CS-1032	CS-1032	CS-1032	CS-1032	CS-1032	CS-1032	CS-1032	CS-1032
馬力(HP)	1	2	3	5	5	7	10	15	20
輸出功率(KW)	0.75	1.5	2.2	3.7	3.7	5.5	7.5	11	15
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	4	4	4	6	6	6	6	6	6
靜壓(mmAq)	450	700	900	1100	790	1050	1300	900	1000
材積(長x寬x高)cm	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160
風量M3/mim(可選配)	13	14	16	16.5	23	24	24	65	70
音量db	60	61	63	64	70	70	75	90	90
容量L(可選配)	40	40	40	40	40	40	40	40	40
主機重量kg	78	86	95	105	112	137	159	245	260

### ■ CS-1033 高壓式水過濾集塵機 HIGH-PRESSURE WATER FILTERING DUST COLLECTOR

型號(MODEL)	CS-1033	CS-1033	CS-1033	CS-1033	CS-1033	CS-1033	CS-1033	CS-1033	CS-1033
馬力(HP)	1	2	3	5	7	10	15	20	25
輸出功率(KW)	0.75	1.5	2.2	3.7	5.5	7.5	11	15	22
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	4	4	4	4	4	4	4	4	4
靜壓(mmAq)	1800	2500	2800	2800	3000	3000	3200	3200	3500
材積(長x寬x高)cm	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160	95x60x160
風量M3/mim(可選配)	2.2	4.5	6.2	8.3	9.5	11	22	24	24
音量db	60	65	65	67	74	74	76	76	76
容量L(可選配)	40	40	40	40	40	40	40	40	40
主機重量kg	72	80	85	105	250	260	350	357	365



## ■ 特點 Features

- 防爆集塵機。
- 針對有燃點或溫度高的粉末或顆粒做降溫的動作。如拋光機或砂輪機所研磨出來之粉末。
- 採用旋風式離心力原理，將粉塵或顆粒吸入下桶。
- 鼓風機純屬抽風效用，吸入物質沒有直接接觸馬達，馬達耐用持久。
- 乾溼兩用。
- 靜音、無燃點問題、無須換濾袋。
- 石墨、纖維、食品、碳粉、鋁粉、農藥、藥品等任何粉末，有無毒性皆可使用，並且可預防粉塵爆炸。
- 鐵屑或銅屑等金屬也可當回收桶(無須前桶)，耐用好清理。
- 各種馬力及大小規格皆有，可視情況需求來搭配。
- 濾心採用PET折疊式濾心材質，過濾面積大，任何細小粉末皆可使用。
- 採用SUS#304材質，裡外光滑亮麗，不會附著粉末，易清理。
- 可過濾至0.1 $\mu$ m(micron)粉末。
- 渦輪式風機可24小時運轉，不會產生高熱。
- 附消音裝置，減少噪音汙染。
- 附壓力表，有無阻塞一目了然。
- Explosion-proof dust collector.
- The dust collector is capable of reducing temperature for powder or granule with some burning point or high temperature, such as powder dusts exhausted from polishing machines or grinders.
- Employ cyclonic centrifugal principle to suck powder or granule into bottom drum.
- The blower is applied for sucking air only. The sucked dusts do not directly contact with motor for increased service life of motor.
- For dry and wet applications.
- Quiet operation. No burning point problem. No need to change filtering bag.
- Suitable for poisonous or non-poisonous dusts such as graphite, fiber, food, carbon powder, aluminum powder, pesticide and medicine. Also featuring anti-explosion of powder.
- Iron chips or copper chips can also be collected (no front tank is required) with maximum durability and easy cleaning..
- Various motor horsepowers and specifications to meet specific requirements.
- The filter-core is manufactured from PET below type filtering element, providing greater filtering area. Applicable for any fine powder.
- Manufactured from SUS#304 material features extremely smooth construction, no powder adhering and easy cleaning.
- The filter-core allows for filtering powder of up to 0.1 $\mu$ m(micron).
- The turbo blower is ideal for 24 hours running without high-temperature growth.
- Equipped with sound buffering device for reducing noise.
- Equipped with pressure gauge for clearly checking if any jamming occurs or not.

若有相關問題，如另設計7.5HP以上 集塵機，如需變更集料方式、儲塵容量、集塵罩、HZ、入口口徑、腳架改不銹鋼等，歡迎來電洽詢，本公司可配合變更或提出更好解決方式。

**If you have any specific requirements (such as dust collector with over 7.5 HP motor, material , collection method, dust hood, air flow, inlet port diameter and storing capacity etc), contact us for further service. We will make design change or provide solutions for your requirements.**



現場實績



# NS-503系列 螺桿式自動脈衝集塵機 SCREW AUTO PULSED DUST COLLECTOR



## ■ NS-503 螺桿式自動脈衝集塵機

型號(MODEL)	NS-503	NS-503	NS-503	NS-503	NS-503	NS-503	NS-503	NS-503	NS-503
馬力(HP)	1	2	3	5	7	10	15	20	25
輸出功率(KW)	0.75	1.5	2.2	3.7	5.5	7.5	11	15	19
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	3	3	3	3	3	3	3	3	3
靜壓(mmAq)	1800	2500	2800	2800	3000	3000	3200	3200	3500
材積(長x寬x高)cm	60x60x170	60x60x170	60x60x170	60x60x170	60x60x170	60x60x170	60x60x170	60x60x170	60x60x170
風量M3/mim(可選配)	2.2	4.5	6.2	8.3	9.5	11	22	24	24
音量db	60	65	65	67	74	74	76	76	76
容量L(可選配)	30	30	30	30	30	30	30	30	30
主機重量kg	225	234	238	253	286	293	383	390	398

## ■ 特點 Features

- 螺桿式移動儲料桶設計，儲料桶放置垃圾袋，直接捆綁倒垃圾，輕鬆清理粉塵。
- 鼓風機純屬抽風效用，吸入物質沒有直接接觸馬達，馬達耐用持久。
- 乾溼兩用，可當一般吸塵器使用。
- 可24小時使用。
- 石墨、纖維、食品、碳粉、鋁粉、農藥、藥品等任何粉末，有無毒性皆可使用。
- 鐵屑或銅屑等金屬也可當回收桶，耐用好清理。
- 高壓脈衝噴射自動清理濾心中間粉塵，粉塵自動振落，可全天候使用。
- 全台首創自動逆衝濾心之集塵機，靜音、無須換濾袋。
- 濾心採用PET折疊式濾心材質，過濾面積大，任何細小粉末皆可使用。
- 各種馬力及大小規格皆有，可視情況需求來搭配。
- 濾心可過濾至0.1μm(micron)粉末。
- 附消音箱裝置，降低噪音污染。

- Screw design of mobile storage tank, storage tank placed garbage bags directly bundled out the trash, clean up dust easily.
- The blower is applied for sucking air only. The sucked dusts do not directly contact with motor for increased service life of motor.
- For dry and wet applications, can be used as normal household vacuum cleaner.
- Allows for 24 hours operation.
- Suitable for poisonous or non-poisonous dusts such as graphite, fiber, food, carbon powder, aluminum powder, pesticide and medicine.
- Iron chips or copper chips can also be collected with maximum durability and easy cleaning.
- High pressure pulsated jet for automatically cleaning dusts existed in the center of filter core. Dusts are knocked off automatically, making it suitable for 24 hours operations.
- The innovative dust collector in Taiwan with automatically pulsated filter-core features silent operation without need to change filtering bag.
- The filter-core is manufactured from PET bellow type filtering element, providing greater filtering area. Applicable for any fine powder.
- Various motor horsepowers and specification to meet specific requirement.
- The filter-core allows for filtering powder of up to 0.1μm(micron).
- Equipped with sound buffering device for reducing noise.

貴公司若有相關問題(如另設計15HP以上集塵機、集料方式、集塵罩、風量、入口口徑、材質、儲塵容量等)，歡迎來電洽詢，本公司可配合變更或提出更好解決方式。

If you have any specific requirements (such as dust collector with over 15 HP motor, collection method, dust hood, air flow, inlet port diameter, material and storing capacity etc), contact us for further service. We will make design change or provide solutions for your requirements.



# CS-350 真空自動吸粉機

## AUTOMATIC POWDER VACUUM SUCTION MACHINE



現場實績



此機可作為中央集塵設備用，  
依現場口徑數量、粉塵多寡、  
搭配馬力大小、桶身大小。



型號(MODEL)	CS-350	CS-350	CS-350	CS-350	CS-350	CS-350	CS-350	CS-350	CS-350
馬力(HP)	1	2	3	5	7	10	15	20	25
輸出功率(KW)	0.74	1.5	2.2	3.7	5.5	7.5	11	15	19
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	2	2	2	2	4	4	4	4	4
輸送能力 (kg/hr) (可選配)	250-1000	250-1000	250-1000	250-1000	1000-2000	1000-2000	2000-3000	2000-3000	3000-4000
濾材尺寸 直徑x長(mm)	325x200	325x200	325x200	325x200	225x600	225x600	225x600	225x600	225x600
過濾網(piece)(可選配)	1	1	1	1	4	4	4	4	6
靜壓(mmAq)	1800	2500	2800	2800	3000	3000	3200	3200	3500
材積(直徑x高)cm(可選配)	45x113	45x113	45x113	45x113	60x135	60x135	60x135	60x135	100x150
風量M3/mim	2.2	4.5	6.2	8.3	9.5	11	22	24	24
音量db	60	66	60	60	100	100	100	100	150
容量L(可選配)	30	30	30	30	70	70	70	70	70

### ■ 特點 Features

- 可依輸送能力不同或儲存容量不同做設計。
- 安全性高，主機不會產生高熱，可輸送各種材料，可24小時運轉。
- 使用高壓空氣噴射，能瞬間震落粉塵不阻塞。
- 該機使用PET折疊式濾心或是PE濾管，有無黏性皆可使用。過濾網會依粉塵性質及特性做更改清洗容易，換料快。
- 採用SUS#304材質，裡外光滑亮麗不會附著粉末，易清除。
- 頂蓋附快速扣環及矽膠迫緊。
- 下料閥附滿料開關。
- 微處理機控制。
- 吸料管嘴及PVC軟管。
- 本公司保留規格變更之權利。
- 吸料和停頓時間可隨需要設定，簡單方便使用。
- 各種馬力皆有，大小容量規格可視情況需求來搭配。
- 濾心可過濾至0.1μm(micron)粉末。

- This machine can be used as a central dust collection equipment, in accordance with the quantity of scene caliber, dust amount, with horsepower, barrel body size
- Custom design for delivery capacity and storing capacity are available.
- Maximum safety. The machine does not generate high temperature suitable for delivering various materials. Ideal for 24 hours running.
- Employs high pressure air jet for instantly knocking off dust without clogging.
- The machine employs PE plastic filter element making it suitable for viscous or non-viscous material. Filter change will be done in accordance with the dust the nature and characteristics
- Easy to clean and change material.
- The machine is manufactured from SUS #304 material, featuring extreme smoothness on inside and outside surface. No dust adhering and easy cleaning.
- The top cover is equipped with quick retainer and fitted with silicon for tightness.
- The unloading valve is equipped with a material fullness sensor.
- Microprocessor control.
- Material suction nozzle and flexible hose.
- Suction inlet pipe and PVC soft pipe
- The machine specifications are subject to change.
- Material suction time and dwell time can be set as desired for added convenience of operation.
- Various motor horsepower and specifications to meet specific requirements.
- The filter core is capable of filtrating powder of up to 0.1μm(micron).

貴公司若有相關問題(如另設計7HP以上吸粉(料)機、輸送能力、靜壓、風量、入口口徑、儲料容量等)，歡迎來電洽詢，本公司可配合變更或提出更好解決方式。

If you have any specific requirements (such as dust collector with over 15 HP motor, collection method, dust hood, air flow, inlet port diameter and storing capacity etc), contact us for further service. We will make design change or provide solutions for your requirements.



# CS-106 旋風式水洗廢氣處理機

## WATER TYPE WASTE GAS COLLECTOR



現場實績



現場實績



現場實績



現場實績



## CS-1061 透浦式水洗廢氣處理機 TURBO WATER TYPE WASTE GAS COLLECTOR

型號(MODEL)	CS-1061	CS-1061	CS-1061	CS-1061	CS-1061	CS-1061	CS-1061
馬力(HP)	1	2	3	5	7.5	10	15
輸出功率(KW)	0.75	1.5	2.2	3.7	5.5	7.5	11
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	6	6	6	6	8	10	12
靜壓(mmAq)	270	320	380	400	600	500	650
材積(長x寬x高)cm	116x76x220	116x76x220	170x80x270	170x80x270	200x133x280	200x133x280	200x133x280
風量M3/mim(可選配)	18	22	40	45	48	75	80
音量db	65	70	75	80	85	85	85
容量L(可選配)	40	40	80	80	80	80	80
主機重量kg	124	132	250-270	250-270	300-325	300-325	300-325

## CS-1062 多段式水洗廢氣處理機 MULTI-STAGE WATER TYPE WASTE GAS COLLECTOR

型號(MODEL)	CS-1062	CS-1062	CS-1062	CS-1062	CS-1062	CS-1062	CS-1062
馬力(HP)	1	2	3	5	5	7	10
輸出功率(KW)	0.75	1.5	2.2	3.7	3.7	5.5	7.5
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	6	6	6	6	6	6	6
靜壓(mmAq)	450	700	900	1100	790	1050	1300
材積(長x寬x高)cm	120x76x220	120x76x220	120x76x220	120x76x220	120x76x220	120x76x220	120x76x220
風量M3/mim(可選配)	13	14	16	16.5	23	24	24
音量db	60	61	63	64	70	70	75
容量L(可選配)	40	40	40	40	40	40	40
主機重量kg	128	136	145	155	162	187	209

## 流程 Working Process

- 廢氣由收集系統抽吸至洗滌塔經水幕及填充物再噴霧三次洗淨後，再經由後段除霧(氣液分離)排出。
- The waste gas is sucked through the dust collection system to the washing tower, in which the waste gas is washed completely through water curtain and 3 times of spray washing. Then they will be exhausted out through the rear mist removing device (gas/fluid separation).

## 特點 Features

- 附消音裝置，降低噪音污染。
- 過濾器可重複清洗使用。
- 主機桶採用不銹鋼材質。
- 主機可將任何溫度高之粉塵或廢氣做到降溫的功能。
- 適用於錫爐、酸洗、侵蝕、電鍍、蝕刻、橡膠、塑膠、化工廠、食品廠、機械加工廠所產生之高溫、惡臭、油氣淨化除臭裝置。
- Equipped with sound buffering device to reduce noise level.
- The filter can be repeatedly washed for reuse.
- The tanks are manufactured from stainless steel.
- Capable of reducing temperature for any high-temperature powder or waste gas.
- Suitable for handling high temperature and odoriferous waste gas and purifying oil mist and removing odor. Applicable for tin furnace, picking, eroding, electro-plating, carving, rubber, plastic, chemical factories, food-processing factories and parts machining factories.



# CS-105

## 超強吸力油霧處理機

### OIL MIST COLLECTOR

採用特大風量和壓力高之鼓風機，  
吸力強速度快，效果更好。  
油氣油水可回收再利用，  
清理更方便。



## ■ CS-1051 透浦式油霧處理機 TURBO TYPE OIL MIST COLLECTOR

型號(MODEL)	CS-1051	CS-1051	CS-1051	CS-1051	CS-1051	CS-1051	CS-1051	CS-1051
馬力(HP)	1	2	3	5	7	10	15	20
輸出功率(KW)	0.75	1.5	2.2	3.7	5.5	7.5	11	15
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	6	6	6	6	8	8	12	12
靜壓(mmAq)	270	320	380	400	450	500	550	550
材積(長x寬x高)cm	110x76x140	110x76x140	110x76x140	110x76x140	100x100x240	100x100x240	200x150x280	200x150x280
風量 M3/mim(可選配)	18	22	40	45	65	70	120	130
音量db	65	70	75	80	85	90	100	105
容量L(可選配)	40	40	40	40	80	80	80	80
主機重量kg	77	84	91	113	298	310	550	570

## ■ CS-1052 多段式油霧處理機 MULTI-STAGE OIL MIST COLLECTOR

型號(MODEL)	CS-1052	CS-1052	CS-1052	CS-1052	CS-1052	CS-1052
馬力(HP)	1	2	3	5	5	7
輸出功率(KW)	0.75	1.5	2.2	3.7	3.7	5.5
電壓 V (可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑 Inch(可選配)	6	6	6	6	6	6
靜壓(mmAq)	450	700	900	1100	790	1050
材積(長x寬x高)cm	110x76x140	110x76x140	110x76x140	110x76x140	100x100x240	100x100x240
風量 M3/mim(可選配)	13	14	16	16.5	23	24
音量db	60	61	63	64	70	70
容量L(可選配)	40	40	40	40	40	40
主機重量kg	83	88	90	97	104	125

## ■ 特點 Features

- 落地式油霧處理機能提高製程上工件之精密度。(沒有因振動而影響工件精密度之困擾。)
- 過濾效果佳，不需時常清理過濾器，過濾器可重複清洗使用。
- 可24小時使用。
- 採用SUS#304材質，裡外光滑亮麗，易清理。
- 各種馬力及大小規格皆有，可視情況需求來搭配。
- 過濾器可重複清洗使用。
- The floor type oil mist collector will upgrades machining accuracy (No vibration to effect machining accuracy).
- Excellent filtrating effect. No need to frequently clean the filter. The filter can be washed and used repeatedly.
- Allows for 24 hours operation.
- Manufactured from SUS#304 material with bright and smooth appearance. Easy to clean.
- Various motor horsepower and specifications to meet specific requirements.
- Filter can be cleaned repeatedly for reuse.
- Suitable for various oil mists created by CNC lathes, milling machines, grinding machines and drilling machines.
- Oil mist and coolant can be reclaimed.
- One collector is used for several machines.
- Powerful suction capacity; high speed.
- Centrifugal Construction: The first stage handles coolant and the second stage handles oil mist to prevent oil mist from splashing out.
- Equipped with sound buffer to reduce noise problem.
- 適用於CNC車床、銑床、磨床、鑽床及各種油氣產生場所。
- 油氣、油水可回收再利用。
- 一機可對多台使用。
- 吸力強、速度快。
- 離心式結構：第一段處理油水部分，第二段處理油氣部分，使油氣不會飛出。
- 附消音管，減少噪音汙染。

# CS-104 脈衝式篩粉機

PULSED DUST SIFTING MACHINE



型號(MODEL)	CS-104	CS-104	CS-104	CS-104	CS-104	CS-104	CS-104
馬力(HP)	1	2	3	5	7	10	15
輸出功率(KW)	0.74	1.5	2.2	3.7	5.5	7.5	11
電壓V(可選配)	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440	220/380 400/440
入口口徑Inch(可選配)	2	2	2	2	(另設計)	(另設計)	(另設計)
輸送能力(kg/hr)	250-1000	250-1000	250-1000	250-1000	(另設計)	(另設計)	(另設計)
濾材尺寸徑x長(mm)	325x200	325x200	325x200	325x200	(另設計)	(另設計)	(另設計)
過濾網(piece)	1	1	1	1	(另設計)	(另設計)	(另設計)
靜壓(mmAq)	1800	2500	2800	3500	3200	3400	3000
材積(長x寬x高)cm	45x113	45x113	45x113	45x113	(另設計)	(另設計)	(另設計)
風量M3/min(可選配)	2.2	4.5	6.2	8.3	9.5	11	24
音量db	60	65	65	67	74	74	76
容量L(可選配)	30	30	30	30	(另設計)	(另設計)	(另設計)
主機重量 kg	70	80	85	105	(另設計)	(另設計)	(另設計)

## ■ 特點 Features

- 過濾網可視實際需求變更。
- 光學鏡頭、藥品、噴砂過濾及其他各種過濾行業。
- 不鏽鋼料桶，質輕耐用好清理。
- 吸料和停頓時間可隨需要設定，簡單容易。
- 空氣壓縮自動除粉，不阻塞，清理方便。
- 各種馬力皆有，大小容量規格可視情況需求來搭配。
- Filtering screen may be changed as desired.
- Applicable for filtration in various industries, such as optical lenses, medicine and sand blasting.
- Stainless steel material tank features light weight. Maximum durability and easy cleaning.
- Material suction and hold time can be set as desired for added convenience.
- Automatic powder removing by compressed air to eliminate clogging while providing convenient cleaning.
- Various motor horsepowers and specification to meet specific requirement.

貴公司若有相關問題(如另設計7HP以上篩粉機、靜壓、風量、入口口徑、儲料容量等)，歡迎來電洽詢，本公司可配合變更或提出更好解決方式。

If you have any specific requirements(such as sifting machine with over 7 HP motor, Static pressure, air flow, inlet port diameter and storing capacity etc), contact us for further service. We will make design change or provide solutions for your requirements.